

Características malla cuadrada



Hueco		Alambre			Peso	%Area abierta
Pul	mm	Nro	Pul	mm	Kg/m2	
1/8	3.17	14	0.080	2.03	10.7	37.2
5/32	3.96	12	0.105	2.67	13.5	36.4
3/16	4.76	11	0.120	3.05	15.7	37.2
		10	0.135	3.43	19.6	33.8
1/4	6.35	11	0.120	3.05	13.7	45.7
		10	0.135	3.43	15.7	42.2
		9	0.148	3.76	18.7	39.4
5/16	7.94	9	0.148	3.76	16.2	46.0
		8	0.162	4.11	18.3	43.4
		6	0.192	4.88	25.1	38.4
3/8	9.52	8	0.162	4.11	16.0	48.7
		6	0.192	4.88	21.5	43.8
7/16	11.11	8	0.162	4.11	14.5	53.2
		6	0.192	4.88	19.6	48.3
1/2	12.7	6	0.192	4.88	17.5	52.2
		4	0.225	5.72	23.4	47.5
		1/4	0.250	6.35	28.1	44.4
5/8	15.87	4	0.225	5.72	19.7	54.0
		1/4	0.250	6.35	25.4	51.0
3/4	19.05	1/4	0.250	6.35	22.0	56.3
		1	0.283	7.19	25.7	52.7
		5/16	0.312	7.94	29.8	49.8
		3/8	0.375	9.52	42.2	44.4
7/8	22.22	1	0.283	7.19	22.7	57.1
		5/16	0.312	7.94	27.2	54.3
		3/8	0.375	9.52	37.6	49.0

Hueco		Alambre			Peso	%Area abierta
Pul	mm	Nro	Pul	mm	Kg/m2	
1	25.40	1	0.283	7.19	20.4	60.8
		5/16	0.312	7.94	26.2	58.0
		3/8	0.375	9.52	36.0	52.9
1.1/4	31.75	5/16	0.312	7.94	22.0	64.0
		3/8	0.375	9.52	30.5	59.2
		7/16	0.437	11.11	37.5	54.8
1.1/2	38.10	3/8	0.375	9.52	26.4	64.0
		7/16	0.437	11.11	32.4	59.9
		1/2	0.500	12.70	37.5	56.3
1.3/4	44.45	3/8	0.375	9.52	23.4	67.8
		7/16	0.437	11.11	28.6	64.0
		1/2	0.500	12.70	39.1	60.5
2	50.80	3/8	0.375	9.52	20.5	70.9
		7/16	0.437	11.11	25.5	67.3
		1/2	0.500	12.70	35.2	64.0
2.1/2	63.50	3/8	0.375	9.52	17.2	75.6
		7/16	0.437	11.11	21.2	72.4
		1/2	0.500	12.70	29.3	69.4
3	76.20	1/2	0.500	12.70	25.1	73.5
		5/8	0.625	15.87	34.0	68.5
3.1/2	88.90	1/2	0.500	12.70	22.0	76.6
		5/8	0.625	15.87	30.0	72.0
		3/4	0.750	19.05	43.0	67.8
4	101.6	1/2	0.500	12.70	19.6	79.0
		5/8	0.625	15.87	26.7	74.8
		3/4	0.750	19.05	38.4	70.9